



TECHNICAL DATA SHEET

Kronos Ultra 15 - Nano Ceramic Ultra Gen3



Kronos Ultra is in the Gen3 (latest generation) window films. It is crystal clear, composed of multiple layers and specially developed for installation on car windows. Using nano-level anti-heat ceramic pigments and implementing them in the different layers creates a special window film with unique properties.

When it comes to comfort, appearance, colorfastness and durability, the Kronos Ultra series is the absolute best in the professional window film industry.

Features

- extremely clear transparency without distortion at an oblique angle
- Lifetime colorfast
- very high heat rejection
- very high infrared (IR) rejection
- UV resistant
- no interference with GPS or other signals
- adheres nicely to the dot matrix
- easily formable by heat shrinking
- roll length: 30,5m

Technical information

 Visible light transmission	16%	 Glare reduction	85%
 Solar energy rejection	67%	 Visible light reflection	6%
 Infra red rejection (760 - 2500 Nm)	85%	 Ultra violet rejected	99%

Warranty

SunRage window films are developed for the professional industry and are known for years of reliability and comfort.



Kronos Ultra gehört zu den Gen3 Auto tönungsfolien (neueste Generation). Sie ist kristallklar, besteht aus mehreren Schichten und wurde speziell für die Anbringung auf Autoscheiben entwickelt. Durch die Verwendung von keramischen Anti-Hitze-Pigmenten im Nanobereich, die in die verschiedenen Schichten eingebracht werden, entsteht eine spezielle Fensterfolie mit einzigartigen Eigenschaften.

Wenn es um Komfort, Ausstrahlung, Farbechtheit und Lebensdauer geht, ist die Kronos Ultra-Serie das absolut Beste, was die professionelle Fensterfolienindustrie zu bieten hat.

Merkmale

- extrem klare Transparenz ohne Verzerrung unter einem schrägen Winkel
- Lebenslang farbecht
- sehr hohe Wärmeabweisung
- sehr hohe Infrarot (IR)-Abweisung
- UV-schützend
- keine Interferenz mit GPS oder anderen Signalenhaftet
- sehr gut an der Punktmatrix
- leicht verformbar durch Wärmeschumpfung
- Rollenlänge: 30,5m

Technische Informationen

 Licht-durchlässigkeit	5%	 Blendung Reduzierung	85%
 Solarenergie Zurückweisung	67%	 Sichtbare Lichtreflektion	6%
 Infra-Rot Ablehnung (760 - 2500 Nm)	85%	 Ultraviolett Zurückweisung	99%

Garantie

SunRage Tuningfolien werden für den professionellen Industrie entwickelt und sind für jahrelange Zuverlässigkeit und Komfort bekannt.



Superior clarity



Easy shrinkage and installation



Good adhesion on the dot matrix

